


FortiRPS™ Redundant Power Supply

FortiRPS 100 and 740



Power supply redundancy is essential in the operation of mission-critical networks. The FortiRPS 100 and 740 are an external redundant power supply designed to increase network availability and uptime. They provide power to supported Fortinet devices should the internal power supply fail.

Supplying up to a total of 552 W and 1178 W of power respectively, the FortiRPS 100 and 740 deliver superior power supply redundancy and resiliency at an affordable price.




Highlights


- Automatic failover delivers High Availability and increased network uptime
- Single rack unit (1 RU) form factor and LED indicators facilitate ease of use and simplifies deployment
- Cost-effective solution supports up to four devices

HARDWARE

FortiRPS 100



FortiRPS 740



SPECIFICATIONS

	FORTIRPS 100	FORTIRPS 740
Dimensions and Power		
Height x Width x Length (inches)	1.75 x 17.0 x 9.29	1.73 x 17.32 x 16.14
Height x Width x Length (mm)	44 x 432 x 236	44 x 440 x 410
Weight	9.5 lbs (4.4 kg)	14.33 lbs (6.5 kg)
Form Factor	1 RU	1 RU
AC Power Supply	100–240V AC, 50–60Hz, 5–2.5A	100–240V AC, 50–60Hz, 12V/14A, 54V/7.8A
Power Budget	552 W	1178 W
Operating Environment		
Operating Temperature	32–122°F (0–50°C)	32–122°F (0–50°C)
Storage Temperature	-4–158°F (-20–70°C)	-40–158°F (-40–70°C)
Humidity	20–85% non-condensing	5–95% non-condensing
Operating Altitude	Up to 7,400 ft (2,250 m)	Up to 7,400 ft (2,250 m)
Supported Devices		
FortiGate	Up to 4 units: FG-310B, FG-300C, FG-100/101E Up to 2 units: FG-200B, FG-200D, FG-240D, FG-300D, FG-400D, FG-500D, FG-600D, FG-200/201E	Up to 2 units: FG-240D-POE and FG-280D-POE
FortiDDoS	Up to 2 units: FDD-200B, FDD-400B, FDD-800B	—
FortiSwitch	Up to 4 units: FS-348B, FS-448B	Up to 2 units: FS-124D-POE, FS-224D-FPOE, FS-248D-FPOE, FS-424D-FPOE
Supplied Accessories		
DC Power Cables	4	2
DC Cable Length	1000 mm	500 mm
AC Power Cables	2	2

ORDER INFORMATION

Product	SKU	Description
FortiRPS 100	FRPS-100	Redundant AC power supply for supported devices, comes with 4x DC cables.
FortiRPS 740	FRPS-740-FG	Redundant AC power supply for up to 2 units of supported FortiGates, comes with 2x DC cables.
	FRPS-740-FS	Redundant AC power supply for up to 2 units of supported FortiSwitches, comes with 2x DC cables.



GLOBAL HEADQUARTERS
Fortinet Inc.
899 KIFER ROAD
Sunnyvale, CA 94086
United States
Tel: +1.408.235.7700
www.fortinet.com/sales

EMEA SALES OFFICE
905 rue Albert Einstein
06560 Valbonne
France
Tel: +33.4.8987.0500

APAC SALES OFFICE
300 Beach Road 20-01
The Concourse
Singapore 199555
Tel: +65.6395.2788

LATIN AMERICA SALES OFFICE
Sawgrass Lakes Center
13450 W. Sunrise Blvd., Suite 430
Sunrise, FL 33323
United States
Tel: +1.954.368.9990